



SF-B150 Series


ANSI
ASME B18.3
ASTM F835~

STAINLESS STEEL 18-8

Rockwell B55~




RoHS Directive Compliance



SOCKET BUTTON SCREW INCH (UNF THREAD)

STAINLESS STEEL 18-8 (B55~ RATED)



Dimension	threads per inch UNRF	dk	k	s	Length
#0	80	.114	.032	.035	From 1/8"
#1	72	.139	.039	.050	from 1/4"
#2	64	.164	.046	.050	from 1/16"
#3	56	.188	.052	.0625	from 1/8"
#4	48	.213	.059	.0625	from 1/8"
#5	44	.238	.066	.0781	from 3/16"
#6	40	.262	.073	.0781	from 1/8"
#8	36	.312	.087	.0937	from 1/8"
#10	32	.361	.101	.1250	from 3/16"
1/4	28	.437	.132	.1562	from 3/16"
5/16	24	.547	.166	.1875	from 1/4"
3/8	24	.656	.199	.2187	from 1/4"
1/2	20	.875	.265	.3125	from 1/2"
5/8	18	1.000	.331	.3750	from 3/4"

Above datas are for reference only

Note:

B150 denotes Stainless Steel 18-8 plain with Rockwell B55~ hardness in UNF series

Part number built example:

e.g. (1) Diameter #10-32 X 3/4" in stainless steel 18-8

» B150 #10X3/4

e.g. (2) Diameter 1/4-28 X 1" in stainless steel 18-8

» B150 1/4X1



sales@synergixfast.com



www.synergixfast.com



Phone: +65 6 316 2630 | Fax: +65 6 316 2730