HEXAGON LOCK NUT WITH NYLON INSERT INCH (UNC & UNF THREAD) THIN TYPE **CARBON STEEL GRADE 5 | ZINC PLATE SYNERGIX**[®] SF-F084 Series (UNC) SF-F085 Series (UNF) F Н Dimension Width (F) Height (H) **CARBON STEEL GRADE 5** 5/8"-11 15/16" 25/64" 5/8"-18 25/64" 15/16" ZINC PLATE 3/4"-10 1 1/16" 13/32" 3/4"-16 1 1/16" 13/32" 7/8"-14 15/32" 1 1/4" 1"-8 35/64" 17/16" 1"-14 17/16" 35/64" 1 1/8"-7 1 5/8" 41/64" 1 1/4"-7 3/4" 1 13/16" 1 1/4"-12 1 7/8" 3/4" 1 1/2"-6 51/64" 2 3/16"







Above datas are for reference only

Note:

F084 denotes unc hex lock nuts thin height in steel grade 5 zinc plate F085 denotes unf hex lock nuts thin height in steel grade 5 zinc plate For use at temperature max. 100 degree (220 Fahrenheit) Size in red color are denoted as unf thread

Part number built example:

e.g. (1) Diameter 5/8-11 in steel g5 zinc plate e.g. (2) Diameter 5/8-18 in steel g5 zinc plate » SF-F084 5/8 » SF-F085 5/8

